



fi-6110

Color Duplex Desktop Scanner

Compact, Efficient, Desktop Scanning.

- True, 600dpi optical resolution with dual-CCDs capture minute details
- 50-page automatic document feeder with double-feed detection
- Fast, 20 ppm (simplex) / 40 ipm (duplex scanning in monochrome and color)
- Includes Adobe Acrobat Standard and ScandAll PRO



For more information, please contact **BizTech Solutions, Inc.**
Tel: 732.761.2880 - Fax: 732.761.3936
Email: sales@forbiztech.com - Web: www.forbiztech.com

The Fujitsu logo consists of the word "FUJITSU" in a bold, red, sans-serif font. Above the letter "i" is a stylized infinity symbol or a pair of interlocking loops.

fi-6110

Color Duplex Desktop Scanner

Get paperwork out of the way with this powerful desktop scanning solution

The Fujitsu fi-6110 scanner's small footprint and advanced feature set make it an ideal solution for decentralized scanning environments. With its true, 600-dpi optical resolution and dual-CCD cameras, it captures your documents' finest details in color, grayscale, and monochrome. What's more, it shares much of the advanced technology found in higher-end scanners, including a 50-sheet automatic document feeder (ADF) that accommodates a wide range of document sizes (2.1 in. x 2.9 in. to 8.5 in. x 14 in.), ultrasonic double-feed detection for greater security, and a Carrier Sheet function for feeding fragile or oversized (A3) documents. Plus at speeds up to 20 ppm (simplex) / 40 ipm (duplex) it quickly and efficiently transforms your paper documents into more manageable digital files. Adobe® Acrobat® Standard and ScandAll PRO utilities are included with the Fujitsu fi-6110 scanner, which allow you to quickly and easily integrate it into your workflow.

Help maximize uptime with service by Fujitsu.

The fi-6110 scanner includes a one-year Limited Warranty and is eligible for our Advance Exchange Program for fast up-time response and total peace-of-mind. For full details on the Limited Warranty and on all service programs, go to www.ImageService.com or call (800) 626-4686.

About Fujitsu Computer Products of America, Inc.

Fujitsu Computer Products of America, Inc., a subsidiary of Fujitsu Ltd., is an established leader in the Document Imaging industry, delivering innovative scanning solutions and services that enable our customers to solve critical business productivity issues and streamline operations. We provide cutting-edge document capture and workflow solutions for business and personal environments, backed by a comprehensive portfolio of service and support programs.

* Statement true as of October 2010



ADOBE® ACROBAT®



Fujitsu Computer Products of America, Inc.

<http://us.fujitsu.com/fcpa>

1250 East Arques Avenue Sunnyvale, CA 94085-4701

(800) 626-4686 (408) 746-7000 info@fcpa.fujitsu.com

Technical Specifications		
Model	fi-6110	
Scanner type	ADF (Automatic Document Feeder)	
Scanning Modes	Duplex / Simplex, Color / Grayscale / Monochrome	
Image Sensor Type	Color CCD (Charge Coupled Device x 2)	
Light Source	White cold cathode discharge lamp	
Optical Resolution	600 dpi	
Output Resolution ¹	Color (24, 8, & 4 bit) ⁷	50 to 600 dpi (adjustable by 1 dpi increments), 1200 dpi ²
	Grayscale (8 bit)	
	Monochrome (1 bit)	
Internal Video Processing	1024 levels (10-bit)	
Image Processing Functions	Auto color detection, Automatic page size detection, Automatic Rotation, Upper lower separation, Multi-image, Blank page skip, Error diffusion, Dither, Dropout color (R, G, B, None, Specified), Image Emphasis, Simplified DTC, Advanced DTC, Moire removal ⁶ , sRGB ⁶	
Scanning Speeds		
Output (Letter/A4 size) ³		Simplex Duplex
Color ⁴	200 dpi & 300 dpi	20 ppm 40 ipm
Grayscale ⁴	200 dpi & 300 dpi	20 ppm 40 ipm
Monochrome	200 dpi & 300 dpi	20 ppm 40 ipm
ADF Capacity ⁵	50 Sheets (letter/A4, 20 lb.) (Active loadable ADF)	
Document size	ADF Minimum	2.1 x 2.9 in. (52 x 74mm)
	ADF Maximum	8.5 x 14 in. (Legal)
	Long Document	8.5 x 34 in. and 8.27 x 120 in. ⁸
Normal	14 to 34 lb. (52 to 127g/m ²) 0.06 to 0.15 mm	
	A8 sheets	34 lb. (0.15 mm) only
Interface	USB 2.0 / USB 1.1 (B type connector)	
Physical Specifications		
Power requirements	100 to 240 VAC ± 10%	
Power consumption	Operating mode: 28W or less (Sleep mode: 5.36W or less)	
Dimensions (WxDxH) ⁹	11.5 x 5.6 x 5.1 in. (292 x 143 x 130 mm)	
Weight	6.61 lb. (3 kg)	
Environmental compatibility	ENERGY STAR® and RoHS ¹⁰	
Operating Environment	Temperature	42°F to 95°F (5°C to 35°C)
	Relative humidity	20 to 80% (non-condensing)
Driver Interface Included	TWAIN, ISIS™	
Bundled Software	Adobe® Acrobat® Standard, ScandAll PRO	
Included Items	AC Adapter, AC Cable, USB Cable, Carrier Sheet, Setup DVD-ROM, Adobe® Acrobat® DVD-ROM, Documentation	
OS Support	Microsoft® 7 (32bit/64bit), Windows Vista™ (32bit/64bit), Windows Server™ 2003/2008 (32bit/64bit), Windows Server™ 2008 R2 (64bit), Windows® XP (32bit/64bit)	
Other Features	Ultrasonic Double Feed Detection Sensor, Long Document Scanning (120 in.) ⁸ , Carrier Sheet Function (Supports A3 and DL size documents)	
Limited Warranty	One-Year Depot. Advance Exchange program also available; restrictions apply. For full details, visit www.ImagengService.com or call (800) 626-4686.	
Service Options	Post-Warranty: Advance Exchange; restrictions apply. Consumables: ScanAid™ kit. For full details, visit www.ImagengService.com or call (800) 626-4686.	
Part Number	PA03607-B005	

1. Maximum output resolutions may vary, depending upon the size of the area being scanned and whether the scanner is scanning in simplex or duplex.
2. Scanning limitations brought about by scanning mode, document size and available memory may occur when scanning at high resolutions (600dpi or higher).
3. Actual scanning speeds are affected by data transmission and software processing times.
4. JPEG compressed figures.
5. Maximum capacity varies depending upon paper weight.
6. The ISIS driver does not support this function.
7. 8bit and 4bit image output through TWAIN driver.
8. The scanning of documents that exceed 34 inches in length will be limited to using TWAIN at 200 dpi or less.
9. Excluding the ADF paper chute and stacker
10. PFU Limited, a Fujitsu company, has determined that this product meets RoHS requirements (2005/95/EC)